Warranty & life time statement

underfloor heating

aquatherm orange system aquatherm green pipe pipe system

For bodily injury

aquatherm lilac pipe pipe system for recycled reclaimed water

aquatherm blue pipe pressure pipe system for chilled and hot applications



aquatherm GmbH manufacture all pipes and fittings in accordance with the German DIN confirming a 50 year guarantee of service life in accordance with the permissible working pressure / temperature of their technical product manuals. Within the scope of this, aquatherm will supply replacement material pipe and fittings if damages are traceable to materials faults and defects.

Liability Warranty

furthermore within the scope of the aquatherm GmbH gives a 10 year guarantee which compensates for material damage to third persons, for investigation, removal, replacement, acceptance, dismounting or laying bare of all defective goods.

aguatherm Gmbh guarantee is conditional on:

- The fusion of joining of pipe and fittings using only aquatherm GmbH welding tools and devices.
- Installation of pipe and fittings are certified aquatherm installers and adherence to aquatherm GmbH technical rules and quidelines for correct installation principles.

15.000.000 Euro

Limits of Liability

	perty damage ccurrence]	15.000.000 Euro
Installation Address:		
Description of Installation:		
Name of Plumber:		
Signature:		
Date of Completion:		
Reg. Installer Number:		

This warranty must be fully completed, signed and returned with the completed test sheet within three months of the completion of the project installation to the New Zealand Agent.

aquatherm® NZ limited, P.O. Box 99 393, Newmarket, Auckland, New Zealand. Phone O9 5707204, Fax O9 570 7206

aquatherm NZ Test record - aquatherm green pipe installation principles

Description c	of the In	stallatio	on
Street Address			
Suburb			
City			
	ı		Y
Type of Installation	Domestic		
	Commerci	al	
	T		Y
Type of Pipe	aquatherm	- , ,	
	aquatherm	blue pipe	
	aquatherm	lilac pipe	
	aquatherm	red pipe	
	aquatherm	grey pipe	
	aquatherm or	ange system	
	,		
Time testing Starte	d		
Time testing finishe			
Test period (minute	s)		
Client:			
	,		
Contractor:			
Installers #:		Date:	
Declaration:			
I declare that I have accordance with aq branding mix			
Signature:			

aquatherm® NZ limited must recieve this information within 3 months of the installation for the waranty to be valid. Please consult with your local area Council as the may require a copy of the test results for the records.

Preliminary Test

[Testing procedure NZ January 2001] Test pressure - 20 bar:

- 1. Test pressure 20 bar 10 minutes.
- 2. Unpressurise for 1 minute.
- 3. Test pressure 20 bar 5 minutes.
- 4. Unpressurise for 1 minute.
- 5. Test pressure 20 bar for 5 minutes.
- 6. Unpressurise.

WARNING

It is imperative to have movement during test period. Tight clips or damaged pipes in frame work will result in an incomplete test which will result in the warranty being invalid.

Result preliminary test:

The test is to be conducted as a continuous test as 20 bar with the five steps noted above.

The system MUST be pressurised THREE TIMES with a minimum rest of one minute between re-pressurising.

If leaking occurs, please replace the part and re start the testing procedure.

The test is complete and acceptable when the above has been undertaken and no leaks are present.

Finally, complete all parts for the test sheet and return a copy to:

aquatherm NZ Limited

P.O. Box 99393, Newmarket, Auckland 1149

www.aquatherm.co.nz. Phone: 09 570 7204 Fax: 09 570 7206